

BTS4000-5V6A Battery testing system											
Model:	BTS4000-	5	V	6	A	BatteryTestingSystem		SN:	CT-4008T	-5V6A	-S1/164
Items					Values						
Input AC					AC 220V/110V ±10% / 50Hz						
Input power					425 W						
Resolution					AD:16bit; DA:16bit						
Input impedance					≥1MΩ						
Voltage	CV output range				25mV~5V						
	Min discharge voltage				1V for universal holder,1.5V for 2m cable						
	Accuracy				± 0.05% FS						
	Stability				± 0.05% FS						
Current	Output range/channel				Range1: 0.5mA-0.1A; Range2: 0.1A-3A; Range3: 3A-6A						
	Accuracy				± 0.05% FS						
	CV cut-off current				Range1: 0.2mA; Range2: 6mA; Range3: 12mA						
	Stability				± 0.05% FS						
Power	Output power/channel				30	W					
	Stability				± 0.1% FS						
Time	Current response time				<1ms (10% FS~90% FS)						
	Working step time				≤(365*24)h/step Timeformat-00:00:00.000(h, m, s, ms)						
Data record	Data record conditions				Min data record interval:100ms						
					Min voltage change: 10mV						
					Min current change: 0.2mA;6mA;12mA						
	Frequency				10Hz						
Charge	Charge modes				CC, CV, CCCV, CP						
	Cut-off condition				Voltage, Current, Time, Capacity, Energy, -△V						
Discharge	Discharge modes				CC, CV, CCCV, CP, CR						
	Cut-off condition				Voltage, Current, Time, Capacity, Energy						
Pulse	Charge				CC, CP						
	Discharge				CC, CP						
	Min pulse width				500ms						
	Pulse counts				Up to 32						
	Chg and Dschg switch				Supported						
	Cut-off condition				Voltage, Time						
DCIR	Calculated DCIR values available in BTSDA										
Cycle	Max cycles				65535						
	Max steps				254						
	Cycle nest				3						
Protection	Safety protection				● Power-failure data protection						
					● Offline operation mode						
					● User-defined protection conditions, such as upper and lower current/voltage, delay time, temperature, etc.						

Channels feature	Independent pairs of closed loop for constant			
Channels control mode	Independent control			
Data acquisition method	Kelvin connection			
Noise	<55dB			
Database	MySQL			
Communication	TCP/IP			
Operating system	Windows 7/8/10 64bit			
Data export	EXCEL, TXT, CSV, PDF, Plot/Graph			
Min. disk drive	500GB			
Communication port	Ethernet port			
Leak Current	<5μA			
Channels per unit	8			
Operation and storage environment requirement				
Items	Values			
Operation environment temperature	0℃~40℃ (When the temperature is 25±10℃, the accuracy offset caused by temperature is less than 50ppm/℃)			
Storage environment temperature	-10℃~50℃			
Operation environment humidity	≤70% RH(no moisture condensation)			
Storage environment humidity	≤80% RH(no moisture condensation)			
Clamps and dimensions				
Items	Values			
Tester pictures				
Clamps pictures				
	Universal holder	Alligator	Polymer	Ring connector
	Pictures just for reference			
Dimensions(W*D*H)(mm)	3U19", 483*404*130			